

MAGIC VISION

MV 9048-812 SD

Compression Data H.264
30% smaller than MPEG-4

Dual Stream Technology

Mobile Viewer

Bi-directional Audio

Email Feature

Support SD Card

Powerfull Recording Software

Auto Tracking Capability



TO OBSERVE & MONITOR
24 Hours ONLINE

Anytime Anywhere

*Supported: Motion Detect - Dual Stream - SD Card Local Recording
Heartbeat - Mobile Viewer - Password Protect - Mouse Control - DDNS*

Security Camera

MV 9048-812 SD

Dengan Teknologi H.264, Magic Vision menawarkan performa kompresi terbaik. H.264 dapat menghapus mosaik dan blur, terutama ketika obyeknya bergerak.

Dengan menggunakan system kompresi ini, kita akan mendapatkan performa 30% lebih baik jika dibandingkan dengan kompresi MPEG-4, yang berarti kita bisa menghemat ruang penyimpanan data sebesar 30%.

Magic Vision IP Camera mendukung Teknologi Dual Stream, dapat diakses melalui telepon genggam. Selain itu, Magic Vision juga mendukung penggunaan SD Card sebagai media penyimpanan data.



Specification

Camera Type	: Speed Dome (Out Door)
Camera Specifications	: 1/4" Sony Super HAD CCD
Effective Pixel	: PAL : 752(H) x 582(V)
Electronic Shutter	: N: 1/50 - 1/10000s (16 Levels)
Lens Type	: Fcl Length: 3.9 - 85.8mm, 22x Optical Zoom, 10x Digital Zoom. Speed: Approx.3.7sec (OWT*), Angular Field of view: 51.2° - 4.2° (WT**), Working Distance: 10 m 1000 mm
Range For Clear View	: ± 100 meters
Pan	: 360° Endless, Speed: Manual: Approx. 0.3°/s - 20°/s, Preset: Up to Approx. 20°/s
Tilt	: 0° - 90°, Speed: Manual: Approx. 0.85°/s - 15°/s, Preset: Up to Approx. 15°/s
Horizontal & Vertical Speed	: 0,3°/s - 20°/s
Min. Illumination	: Color: Less equal to 1 Lux
Video Output	: Test Monitor OUT 1Vp-p Composite Output (75Ω/BNC)
Image Size	: PAL: 704 x 576, 640 x 480, 528 x 384, 704 x 288, 176 x 144
Frame Rate	: 25 fps (704 x 576)
Video Compression	: H.264
Video Output	: 32 K-2M, adjustable (8Mbps Maximum)
Audio Output	: OggVorbis / 16 Kbps
Voice Talk Input	: 1 channel (2.0-2.4Vp-p, 1kΩ)
Voice Output	: 1 channel (Line Level, 600Ω)
Communication	: 1 RJ45 10M / 100M self-adaptive Ethernet port, 1 RS-485 interface
Alarm Input	: 1 Channel Input
Alarm Output	: 1 Channel Output, alarm linkage is configurable
Weight	: 5 Kg
Dimension (mm)	: 6 inch, Ø243 (mm) x 287 (mm)
Power Requirement	: 24VAC (12VDC option) / POE
Power Consumption	: 12W (50W Heater ON)
Working Temperature	: 10° - 60° (Outdoor)
Feature (Optional)	: Vandal Proof
Supporting IP Protocol	: TCP/IP, UDP/IP, RTSP, FTP, SMTP, DHCP, NTP, SNMP